



metal
FREE

ROBORIS
007AX13

S3 SRC
EN ISO 20345:2011
36 to 47

Low shoe
Urban sport



- Ⓜ Low urban sport safety shoe, black colour. PU toe protection in front.
- Ⓜ Upper in water-resistant leather, grained finish, 1.9 / 2.1mm thick.
- Ⓜ **3D.LINING**® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- Ⓜ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- Ⓜ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- Ⓜ Fastened by lacing through 5 pairs of perforations. Laces 90 cm 36 to 41 and 110 cm 42 to 47.
- Ⓜ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- Ⓜ Complete **VENTO-PLUS**® anatomical and antistatic inlay, with honeycomb structure for improved air circulation.
- Ⓜ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL**® orthopaedic insole.
- Ⓜ Stab-proof non-metallic **FLEX-SYSTEM**® liner : total protection of the sole of the foot.
- Ⓜ **LIGHT-PLUS**® protective toecap in synthetic material offering protection from an impact of 200 J.



Slip resistance tests results

EN Standard : EN ISO 20345 : 2011 **Requirement SRC**
(SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent
On flat **0,49** (>0,32) – On the heel **0,35** (>0,28)

SRB Test ground steel / lubricant : glycerine
On flat **0,26** (>0,18) – On the heel: **0,18** (>0,13)

W-Tech Wrapping Technology sole in PU dual density :

- Resists oils and hydrocarbons .
- Slim, streamlined profile rising towards the toes.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking



Weight	Gross Weight (42) : 1312 g / Net weight (42) : 1094 g			
Size	38 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Dimensions (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions box (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350