



ARTIS
7AX70

S3 SRC
EN ISO 20345:2011
36 to 47

Low shoe
Trekking

DOMINUS

3D Lining

Light PLUS

COMFORT PLUS

FLEX system ZERO

W-TECH

metal FREE

- ⊗ Low trekking safety shoe, brown colour. PU toe protection in front and anti-abrasion leather for strength and long life.
- ⊗ Upper in finest-quality water-resistant leather, 1.9/2.1 mm
- ⊗ **3D.LINING**® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ⊗ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ⊗ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- ⊗ Fastened by lacing through 5 pairs of perforations. Laces 100 cm 36 to 40 and 110 cm 41 to 47.
- ⊗ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- ⊗ Complete **CONFORT PLUS**® inlay, antistatic and anatomically shaped in flexible polyurethane covered in breathable, absorbent fabric.
- ⊗ Stab-proof non-metallic **FLEX-SYSTEM**® liner : total protection of the sole of the foot.
- ⊗ **LIGHT-PLUS**® protective toecap in synthetic material offering protection from an impact of 200 J.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant :
water and detergent

On flat **0,44** (>0,32) – On the heel **0,37**
(>0,28)

SRB Test ground steel / lubricant :
glycerine

On flat **0,19** (>0,18) – On the heel:
0,15 (>0,13)

W-Tech Wrapping Technology sole in PU dual density :

- Resists oils and hydrocarbons .
- Slim, streamlined profile rising towards the toes.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking

Weight	Gross weight (42): 1294 g / Net weight (42): 1076 g		
Size	36 to 39	40 to 45	46 to 47
Packaging	5 pairs	10 pairs	5 pairs
Dimensions	700x255x360	700x510x360	700x255x360