


 S2 FO SR
 EN ISO 20345:2022
 35 to 48

 Low-top shoe
 Type loafer


WAT-OUT

3D Lining

Light PLUS

Vento PLUS

metal FREE

- Loafer shoes ideal for food industry jobs. Black color.
- Shaft made of synthetic material **WAT-OUT®**, highly breathable, water-repellent and hypoallergenic. Can be washed with soap and water.
- **3D.LINING®** lining made from a 3-layer material for improved moisture wicking, high breathability and quick drying.
- Vamp lined in non-woven fabric. Resists scuffing and acid perspiration.
- Ergonomic padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection.
- Snug fit thanks to elastic band underneath protective tongue.
- Complete **VENTO-PLUS®** anatomical and antistatic inner lining with honeycomb structure for improved air circulation.
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- Inner sole antistatic.
- **LIGHT-PLUS® B** safety toe cap made of synthetic material protecting against impacts of up to 200 J. Minimum height after test $\geq 4\text{mm}$ in relation to the Type A toe cap in accordance with **Standard 22568-2:2019**.

Slip resistance tests results EN Standard ISO 20345:2022

Test ground : Ceramic / NaLS (Sodium lauryl sulfate)

- A- Heel to the front **0,31** ($>0,45$)
- B- Front to back **0,36** ($>0,41$)

Additional requirement **SR** : Ceramic / Glycerin

- C- Heel to the front **0,19** ($>0,39$)
- D- Front to back **0,22** ($>0,32$)

Dual-density PU outsole :

- Resists grease and cleaning products.
- Abrasion resistant.
- Treads with crossed channels th help shed water.



Weight	Gross weight (42) : 1118 g / Net weight(42) : 900 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		335 x 210 x 130	
Cartons (mm)	592 x 212 x 313	592 x 410 x 313	685 x 440 x 356	680 x 234 x 356