



FLAG
7SP02

S3 SRC
EN ISO 20345:2011
38 to 47

Low shoe
Trekking



SUPREME

- ⊗ Low trekking safety shoe, colour black. PU toe protection in front .
- ⊗ Upper in water-resistant leather, grained finish, 1.9 / 2.1mm thick.
- ⊗ **3D.LINING**® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ⊗ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ⊗ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- ⊗ Lace up on four pairs of non-metallic lace stays . Laces 100 cm.
- ⊗ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- ⊗ Fluorescent markings on the back of the heel for increased visibility when doing night work.
- ⊗ Complete **CONFORT PLUS**® inlay, antistatic and anatomically shaped in flexible polyurethane covered in breathable, absorbent fabric.
- ⊗ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL**® orthopaedic insole.
- ⊗ Stab-proof non-metallic **FLEX-SYSTEM**® liner : total protection of the sole of the foot.
- ⊗ **LIGHT-PLUS**® protective toecap in synthetic material offering protection from an impact of 200 J.
- ⊗ Antistatic and non-magnetic shoe.



Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant :
water and detergent

On flat **0,38** (>0,32) – On the heel **0,31**
(>0,28)

SRB Test ground steel / lubricant :
glycerine

On flat **0,20** (>0,18) – On the heel:
0,17 (>0,13)

Sole in PU dual density :

- Resists oils and hydrocarbons .
- Absorption of heel impact > 20 joules.
- Outdoor profile for better stability when walking.
- Maximum confort.

Weight	Gross weight (42) : 1378 g / Net weight (42) : 1170 g		
Size	38 à 39	40 à 45	46 à 47
Packaging	5 pairs	10 pairs	5 pairs
Dimensions (mm)	360 x 220 x 700	360 x 440 x 700	360 x 220 x 700
Dimensions box (mm)	340 x 210 x 133		