



**INOX
7SP06**

**S3 SRC
EN ISO 20345:2011
38 to 48**

**High shoe
Water-repellent full-grain leather upper**

SUPREME

STARK®

3D Lining

**CLASSIC
PLATE**

**Light
PLUS**

**COMFORT
PLUS**

- ⊗ High shoe, basket type, brown colour. PU toe protection in front.
- ⊗ Water-repellent full-grain leather pull-up finish upper Thickness 1,9 / 2,1. Protective Stark scuff cap reinforcement to vamp for strength and long life in very demanding conditions: improved resistance to impacts, cuts and abrasion. Anti-abrasion PU scuff cap.
- ⊗ **3D.LINING®** in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- ⊗ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- ⊗ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- ⊗ Lace up on five pairs of lace stays. Laces 120 cm.
- ⊗ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- ⊗ Complete **CONFORT PLUS®** inlay, antistatic and anatomically shaped in flexible polyurethane covered in breathable, absorbent fabric.
- ⊗ Stainless rustproof steel midsole.
- ⊗ **LIGHT-PLUS®** protective toecap in synthetic material offering protection from an impact of 200 J.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,38** (>0,32) – On the heel **0,31** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,20** (>0,18) – On the heel: **0,17** (>0,13)

Sole in PU dual density :

- Resists oils and hydrocarbons .
- Self-cleaning sole and deep multi-directional treads.
- Absorption of heel impact > 20 joules
- Wrap-around profile for better stability when walking

Weight	Gross Weight (42) : 1588 g / Net Weight (42) : 1380 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350

