

24 BIT



**DRAKE
00ABI02**



**S1P SRC
EN ISO 20345:2011
38 to 47**

**Sporty urban safety shoes
Antistatic**



SOFT

DURABREATH

OVERDRY

ALULITE

**FLEXsystem
ZERO**

- Black and grey sporty urban safety shoes .
- Suede leather upper and textile DURABREATH inserts.
- Upper lined in technical textiles OVER DRY, very resistant and high breathability.
- Vamp lined in non-woven fabric.
- Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection..
- Fluorescent markings for increased visibility when doing night work.
- Closure by laces. Laces : 120 cm.
- Padded and lined textile tongue for instep protection with side bellows to keep out dust and dirt.
- **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical and breathable.
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole
- provided for a **SECOSOL®** orthopaedic insole.
- **FLEX-SYSTEM®** Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- **ALU-LITE®** 200 J aluminium safety toe cap, anti corrosion and 50% lighter than steel material.

98GRIP



Dual density PU sole , outsole in PU transparent.

- ▶ Out-sole design featuring specific transversal grooves, high performance of slip resistance.
- ▶ Resistant to oils and hydrocarbons.
- ▶ Sporty profile and design.
- ▶ Heel shock absorption > 20 Joules.

Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant : water and detergent

On flat **0,98** (>0,32) – On the heel **0,74** (>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,40** (>0,18) – On the heel: **0,35** (>0,13)

Weight	Gross Weight (42) : 1254 g / Net Weight (42) : 1046 g			
Size	38 to 39	40 to 41	42 to 45	46 to 47
Packaging	5 pairs		10 pairs	
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350