

24 BIT



**BIGGIE
00ABI03**

**S3 SRC
EN ISO 20345:2011
38 to 47**

**Black sporty urban safety shoes
Antistatic**



SOFT

OVERDRY

ALULITE®

**FLEX system[®]
ZERO**

- Black sporty urban safety shoes .
- Water-repellent full-grain leather upper, pull-up finish.
- Upper lined in technical textiles OVER DRY, very resistant and high breathability.
- Vamp lined in non-woven fabric.
- Padded collar with compact flexible foam for extra comfort and better ankle and Achilles tendon protection..
- Fluorescent markings for increased visibility when doing night work.
- Closure by laces. Laces : 120 cm.
- Bellows tongue for superior waterproofing. Padded tongue to protect the top of the foot.
- Soft footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical and breathable.
- This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- **FLEX-SYSTEM®** Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- **ALU-LITE®** 200 J aluminium safety toe cap, anti corrosion and 50% lighter than steel material.

98GRIP



Slip resistance tests results

EN Standard : EN ISO 20345 : 2011
Requirement SRC (SRA+SRB)

SRA Test ground : ceramic / lubricant :

water and detergent

On flat **0,98** (>0,32) – On the heel **0,74**
(>0,28)

SRB Test ground steel / lubricant : glycerine

On flat **0,40** (>0,18) – On the heel: **0,35**
(>0,13)

Dual density PU sole , outsole in PU transparent.

- ▶ Out-sole design featuring specific transversal grooves, high performance of slip resistance.
- ▶ Resistant to oils and hydrocarbons.
- ▶ Sporty profile and design.
- ▶ Heel shock absorbtion > 20 Joules.

Weight	Gross Weight (42) : 1338 g / Net Weight (42) : 1130 g		
Size	38 to 39	40 to 41	42 to 45
Packaging	10 pairs		
Box (mm)	306 x 192 x 114		340 x 210 x 133
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350
			680 x 215 x 350