



- Urban sport-style safety shoe incorporating **MAXI-Soft Duo™** anti-fatigue technology designed for work stations that require standing for long periods (Upright or sustained activity).
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- Water-repellent full-grain leather upper. Fluorescent markings on the back of the heel. Black color.
- Lining of the quarters in **OVER DRY** technical textile, very resistant and highly breathable.
- Non-woven textile forefoot lining.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Lace up on 5 pairs of non metal eyelets and 2 pairs of hooks **Quick Lio (maintain the lace in place and allows quick lacing and unlacing)**. Black laces 160 cm.
- Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- **Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the Link ESD™ system, an innovative and seamless, multi-contact static electricity dissipater (Patent pending).
- **FLEX-SYSTEM®** Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- **LIGHT-PLUS®** protective toecap in synthetic material offering protection from an impact of 200 J



- **BASF® PU/PU** sole with an urban sport design, linear profile and excellent slip resistance.
- Extremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.

#### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

Requirement SRC (SRA+SRB)

**SRA** Test ground : ceramic / lubricant : water and detergent

On flat **0,47** (>0,32)-On the heel **0,34** (>0,28)

**SRB** Test ground steel / lubricant : glycerine

On flat **0,33** (>0,18)-On the heel **0, 21** (>0,13)

Weight	Gross Weight (42) : 1496 g / Net Weight (42) : 1290 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box (mm)	340 x 210 x 133		340 x 245 x 133	
Dimensions (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359