



- Low safety shoe, loafer type incorporating **MAXI-Soft Duo™** anti-fatigue technology designed for work stations that require standing for long periods (Upright or sustained activity).
- Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- Microfibre upper, easy to clean with soap and water, good resistance to fluids. White colour. Doublure des quartiers en textile technique **OVER DRY**, très résistant et haute respirabilité .
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Elasticated fastening for easy adjustment around the ankle joint.
- Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of a soft **BASF® Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan insert** that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESD™ system**, an innovative and seamless, multi-contact, static electricity dissipater. (Patent pending).
- **FLEX-SYSTEM®** Stab-resistant structural insole and liner antistatic and 100% composite in compliance with standard 12568:2010.
- **LIGHT-PLUS®** protective toecap in synthetic material offering protection from an impact of 200 J



- **BASF® PU/PU** sole with an urban sport design, linear profile and excellent slip resistance.
- Extremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.

### Slip resistance tests results

EN Standard : EN ISO 20345 : 2011

**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent  
On flat **0,47** (>0,32)-On the heel **0,34** (>0,28)

**SRB** Test ground steel / lubricant : glycerine  
On flat **0,33** (>0,18)-On the heel **0, 21** (>0,13)

Weight	Gross Weight (42) : 1316 g / Net Weight (42) : 1100 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs		10 pairs	
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350