



\* Brevet International



- High safety shoe of loafer type designed with **BASF's innovative High Rebound technology**.
- Electrostatic dissipative shoes **ESD** Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- Synthetic **WAT-OUT®** upper, optimal breathability, water resistant and antiallergenic. Washable in soap and water.
- Breathable upper lining in **3D** mesh, with honeycomb structure for improved all-round ventilation of the foot and fast-drying.
- Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- Snug fit thanks to elastic band underneath protective tongue.
- Soft** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative and seamless, multi-contact static electricity dissipater (Patent pending).
- FLEX-SYSTEM®** Stab-resistant structural insole and liner antistatic and 100% composite in compliance with **standard 12568:2010**.
- ALU-LITE®** tip in aluminium resisting an impact of an energy of 200 joules.



**BASF Extra Rebound 41.5** innovative sole, with 2 layers of PU, new technology which returns over **40% energy** with every step :

- Less feeling of fatigue during prolonged periods of activity.
- Extremely soft and supple support base for lightweight and optimum comfort.
- Constant energy return provided over the entire surface of the foot.



**Slip resistance tests results**  
EN Standard : EN ISO 20345 : 2011  
**Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent  
On flat **0,41** (>0,32)–On the heel **0,30** (>0,28)

**SRB** Test ground steel / lubricant : glycerine  
On flat **0,18** (>0,18)–On the heel: **0,15** (>0,13)

Weight	Gross Weight (42) : 1228 g / Net Weight (42) : 1000 g			
Size	35 - 39	40 - 41	42 - 45	46 - 48
Packaging	5 pairs		10 pairs	
Box (mm)	306 x 192 x 114		340 x 210 x 133	
Dimensions (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350