



**metal
FREE**

**AVANGER
DM10184**

**S3 CI SRC
EN ISO 20345:2011
35 to 47**

**Hight shoe
Putek® textile**

PU Tek PLUS*
HYPERTEX technology

STARK®

3DLining

Light PLUS

VENTO PLUS

FLEXsystem ZERO

- Ⓢ Black and grey sporty urban safety shoes, extremely lightweight.
- Ⓢ Putek® PLUS textile upper, high resistance to abrasion, heel in Stark® anti-abrasion.
- Ⓢ 3D.LINING® in three-ply material for improved evacuation of moisture to the exterior, high breathability and fast-drying.
- Ⓢ Vamp lining in non-woven fabric. Resists abrasion and acid perspiration.
- Ⓢ Padded collar. Provides comfort to the ankle-bones and protects the Achilles tendon.
- Ⓢ Lace up by laces 120 cm.
- Ⓢ Padded tongue to provide better protection to the instep, combined with two side gussets to prevent grit from entering the shoe.
- Ⓢ Complete VENTO-PLUS® anatomical and antistatic inlay, with honeycomb structure for improved air circulation.
- Ⓢ Stab-proof non-metallic FLEX-SYSTEM® liner : total protection of the sole of the foot.
- Ⓢ LIGHT-PLUS® protective toecap in synthetic material offering protection from an impact of 200 J.

DIAMONT Sole in PU dual density BASF last generation :

- ▶ Resists oils and hydrocarbons
- ▶ Linear profile, comfort, lightness and versatility
- ▶ Absorption of heel impact > 20 joules
- ▶ Streamlined profile rising towards the toes



Slip resistance tests results	
EN Standard : EN ISO 20345 : 2011 Requirement SRC (SRA+SRB)	
SRA Test ground : ceramic / lubricant : water and detergent	
On flat 0,40 (>0,32) – On the heel 0,40 (>0,28)	
SRB Test ground steel / lubricant : glycerine	
On flat 0,18 (>0,18) – On the heel: 0,16 (>0,13)	

Weight	Gross weight (42) : 1108 g / Net weight (42) : 880 g			
Size	35 to 39	40 to 41	42 to 45	46 to 47
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	340 x 210 x 133		340 x 245 x 133	
Cartons (mm)	685 x 225 x 359	685 x 440 x 359	685 x 505 x 359	685 x 255 x 359