



S2 FO SR
EN ISO 20345:2022
35 to 48

High shoe
Antistatic



* International Patent



metal
FREE

OVERDRY

SOFT

Light
PLUS

- 🕒 High-top safety shoe of loafer type designed with **anti-fatigue technology**.
- 🕒 Synthétic **WAT-OUT®** upper, optimal breathability, water resistant and antiallergenic. Washable in soap and water. Color white
- 🕒 Upper lined in breathable textile **OVER DRY**, very resistant and better foot ventilation .
- 🕒 Ergonomic padded collar with compact flexible foam for extra comfort ankle and Achilles tendon protection.
- 🕒 Snug fit thanks to elastic band underneath protective tongue.
- 🕒 Soft footbed made of **BASF® Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical and breathable.
- 🕒 This is a DGUV 112-191 certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole..
- 🕒 **LIGHT-PLUS® B** safety toe cap made of synthetic material protecting against impacts of up to 200 J. Minimum height after test \geq 4mm in relation to the Type A toe cap in accordance with Standard **22568-2:2019**.



VIGOREX sole made of dual-component PU / and BASF's Infinergy® E-TPU insert ;

- ▶ E-TPU insert at low density of 0.25.
- As elastic as rubber but lighter.
- High resistance to abrasion and stretching.
- Good chemical resistance.
- Long-term durability in a wide temperature range.
- Exceptional resilience (high capacity to return energy).



Slip resistance tests results
EN Standard : EN ISO 20345:2022

Ceramic / Laurylsulfate de sodium
A - **0,42** ($>0,31$) / B - **0,36** ($>0,36$)

Exigence additionnelle **SR**
Ceramic / Glycerine
C - **0,31** ($>0,19$) / D - **0,27** ($>0,22$)

Weight	Gross weight (42) : 1110 g / Net weight (42) : 902 g			
Size	35 to 39	40 to 41	42 to 45	46 to 48
Packaging	5 pairs		10 pairs	5 pairs
Box shoes (mm)		335 x 210 x 130		335 x 245 x 130
Cartons (mm)	680 x 234 x 356	685 x 440 x 356	680 x 514 x 356	685 x 256 x 356