


 S2 FO SR  
 EN ISO 20345:2022  
 35 to 48

 Low shoe  
 Antistatic


\*International Patent



- Low safety shoe of loafer type designed with **anti-fatigue technology**.
- Synthétique **WAT-OUT®** upper, optimal breathability, water resistant and antiallergenic. Washable in soap and water. Color white
- Upper lined in breathable textile **OVER DRY**, very resistant and better foot ventilation.
- Ergonomic padded collar with compact flexible foam for extra comfort ankle and Achilles tendon protection.
- Snug fit thanks to elastic band underneath protective tongue.
- Soft footbed made of **BASF® Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical and breathable.
- This is a DGUV 112-191 certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole..
- **LIGHT-PLUS® B** safety toe cap made of synthetic material protecting against impacts of up to 200 J. Minimum height after test  $\geq 4\text{mm}$  in relation to the Type A toe cap in accordance with Standard **22568-2:2019**.



VIGOREX sole made of dual-component PU / and BASF's Infinergy® E-TPU insert ;

▶ E-TPU insert at low density of 0.25.

- As elastic as rubber but lighter.
- High resistance to abrasion and stretching.
- Good chemical resistance.
- Long-term durability in a wide temperature range.
- Exceptional resilience (high capacity to return energy).



New Infinergy by BASF

**Slip resistance tests results**  
 EN Standard : EN ISO 20345:2022

 Ceramic / Laurylsulfate de sodium  
 A - **0,42** ( $>0,31$ ) / B - **0,36** ( $>0,36$ )

 Exigence additionnelle SR  
 Ceramic / Glycerine  
 C - **0,31** ( $>0,19$ ) / D - **0,27** ( $>0,22$ )

Weight	Gross weight (42) : 1110 g / Net weight (42) : 902 g		
Size	35 to 39	40 to 41	42 to 45
Packaging	5 pairs	10 pairs	5 pairs
Box shoes (mm)	306 x 192 x 114		335 x 210 x 130
Cartons (mm)	592 x 212 x 313	592 x 410 x 313	685 x 440 x 356
			680 x 234 x 356